CT-1011-H2

Highly compact, high-speed, electrically driven radial turbo compressor with gas bearing for the circulation and compression of a mixture of nitrogen, hydrogen and water (vapor).

- High-speed gas bearings for oil-free operation
- Lowest ratio of volume and weight versus pressure and mass flow due to highest speeds
- Aerodynamic and electromagnetic optimization for highest total efficiency
- Integrated temperature measurement for overload protection
- Compatible to frequency converter CC-230-3500



Specifications turbo compressor	
Maximum pressure ratio	1.15
Maximum mass flow	16 g/s
Maximum isentropic overall efficiency[1]	65 %
Maximum speed	180,000 rpm
Maximum compressor input power	510 W
Weight	8 kg
Dimensions (L x W x H)	182 x 277 x 175.2 mm (7.17 x 10.9 x 6.9 inch)

Cooling	
Coolant	50 %/50 % water glycol mixture
Coolant temperature	75 °C
In-/Outlet connector typed	G 3/8

Electrical interface	
Connection type	Motor cable with inline circular connector
Connector type	Hummel M23 TWILOCK cable connector

[1]Isentropic overall efficiency including aerodynamic, motor and bearing efficiency

All rights reserved. All information in this document is based on Celeroton's best knowledge and is not to be considered as a warranty or quality specification. The information given is designed as a guidance and customers are requested to check the suitability and usability of the product in their specific application with consulting Celeroton. The information herein is subject to change without notification.

Compressor map

Pressure ratio versus mass flow	Compressor input power versus mass flow





Order codes: CT-1011-H2

Ordering information	Article number
CT-1011-H2	4010060
CT-1011-H2 with CC-230-3500	4040087

Order Codes: option

Ordering information	Article number
CT-1011-H2 drainage piping	Contact Celeroton

All rights reserved. All information in this document is based on Celeroton's best knowledge and is not to be considered as a warranty or quality specification. The information given is designed as a guidance and customers are requested to check the suitability and usability of the product in their specific application with consulting Celeroton. The information herein is subject to change without notification.

Drawing in mm [inch]



All rights reserved. All information in this document is based on Celeroton's best knowledge and is not to be considered as a warranty or quality specification. The information given is designed as a guidance and customers are requested to check the suitability and usability of the product in their specific application with consulting Celeroton. The information herein is subject to change without notification.

Drawing with option drainage piping in mm [inch]



i	The specifications and compressor maps in this document refer to a mixture of 61 mol-% hydrogen, 24 mol-% nitrogen and 15 mol-% water (vapor) at the inlet of the compressor: temperature: $T = 75\ °C$, absolute pressure: $p_{in} = 2.0\ bara$.
i	Depending on custom specific operation conditions such as e.g. gas inlet pressure and temperature, humidity, cooling conditions, the operation in environmental conditions with vibrations and/or depending on the combination of the compressor and the corresponding Celeroton converter, the compressor maps shown in this document may be different or may have additional limitations. For technical details and further information, please refer to the user manual or contact Celeroton directly.

Celeroton AG | Industriestrasse 22 | 8604 Volketswil | Switzerland
T: +41 44 250 52 20 | info@celeroton.com

All rights reserved. All information in this document is based on Celeroton's best knowledge and is not to be considered as a warranty or quality specification. The information given is designed as a guidance and customers are requested to check the suitability and usability of the product in their specific application with consulting Celeroton. The information herein is subject to change without notification.